

ANNKE C800 Bullet No-Audio Specifications (Model Number: I918D)	
Image Sensor	1/2.5" Sony Progressive Scan CMOS
Video Resolution	8MP (3840 X 2160@15 fps)
Signal System	PAL/NTSC
Video Compression	H.265/H.264
Video Bitrate	32 Kbps - 16 Mbps
Lens	2.8 mm
Min. Illumination	0.01 Lux @(F1.2, AGC On)
Angle of View	102°
Number of Infrared LEDs	2 pcs
Night Vision Distance	Up to 100 ft/30 m
DNR	3D DNR
Wide Dynamic Range	Digital WDR
ONVIF	Support
IR-Cut Filter	Yes
Ethernet	RJ45 X1 (10 M/100 M)
Housing	Metal
Color	White
Operating Power	PoE (802.3af)
Operating Temperature	-22 °F ~ 140 °F/30 °C ~ 60 °C
Indoor/Outdoor	Indoor/Outdoor
Weatherproof Rating	IP67
Dimension	6.1" X 2.8"/155 X 70 mm
Weight	0.9 lb./410 g

C800 Bullet Audio Version Specifications (Model Number: I918L)	
Image Sensor	1/2.5" Progressive Scan CMOS
Video Resolution	50 Hz: 12.5 fps (3840 X 2160, 2560 X 1440, 1920 X 1080, 1280 X 720) 60 Hz: 15 fps (3840 X 2160, 2560 X 1440, 1920 X 1080, 1280 X 720)
Sub Stream	50 Hz: 25 fps (640 X 480, 640 X 360) 60 Hz: 30 fps (640 X 480, 640 X 360)
Video Compression	H.265+/H.265
Video Bitrate	32 Kbps - 16 Mbps
Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC
Audio Input/Output	Built-in Microphone
Lens	2.8 mm
Min. Illumination	0.01 Lux @(F2.0, AGC On)
Angle of View	Horizontal Fov 102°, Vertical Fov 53°, Diagonal Fov 123°
Number of Infrared LEDs	2 pcs
Night Vision Distance	Up to 100 ft/30 m
DNR	3D DNR
Wide Dynamic Range	120 dB WDR
Network Storage	Local Storage & NAS (NFS, SMB/CIFS)
ONVIF	Support
Day/Night Switch	Day, Night, Auto, Schedule
Ethernet	RJ45 X1 (10 M/100 M)
Housing	Aluminum Alloy for Main Body
Color	White
Operating Power	PoE (802.3af), 12 V DC ± 25%
Storage	Built-in MicroSD/SDHC/SDXC Slot, up to 256 GB
Hardware Reset	Yes
Operating Temperature	-22 °F ~ 140 °F/30 °C ~ 60 °C
Indoor/Outdoor	Indoor/Outdoor
Weatherproof Rating	IP67
Dimension (L X W X H)	171.4 X 69.7 X 67.9 mm (6.7" X 2.7" X 2.7")
Weight	0.9 lb./430 g

C800 Turret No-Audio Version Specifications (Model Number: I918F)	
Image Sensor	Sony 1/2.5" Progressive Scan CMOS
Video Resolution	8MP (3840 X 2160)
Signal System	PAL/NTSC
Video Compression	H.265+/H.265/H.264+/H.264
Video Bitrate	32 Kbps ~ 16 Mbps
Lens	2.8 mm
Min. Illumination	0.01 Lux @(F1.2, AGC On)
Angle of View	Diagonal Fov: 124°
Number of Infrared LEDs	1 pc
Night Vision Distance	Up to 100 ft/30 m
DNR	3D DNR
Wide Dynamic Range	120 dB True WDR
ONVIF	Support
IR-Cut Filter	Yes
Ethernet	RJ45 X1 (10 M/100 M)
Housing	Metal & Plastic
Color	White
Operating Power	DC 12 V; PoE (802.3af)
Storage	Built-in microSD/SDHC/SDXC Slot, up to 128 GB
Operating Temperature	-22 °F ~ 140 °F/30 °C ~ 60 °C
Indoor/Outdoor	Indoor/Outdoor
Weatherproof Rating	IP67
Dimension (L X W X H)	5" X 3.8"/127.3 X 95.9 mm
Weight	1.4 lbs./620 g

ANNKE C800 Turret Audio Version Specifications (Model Number: I918M)	
Image Sensor	1/2.5" Progressive Scan CMOS
Video Resolution	50 Hz: 12.5 fps (3840 X 2160, 2560 X 1440, 1920 X 1080, 1280 X 720) 60 Hz: 15 fps (3840 X 2160, 2560 X 1440, 1920 X 1080, 1280 X 720)
Sub Stream	50 Hz: 25 fps (640 X 480, 640 X 360) 60 Hz: 30 fps (640 X 480, 640 X 360)
Video Compression	H.265+/H.265
Video Bitrate	32 Kbps ~ 16 Mbps
Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC
Audio Input/Output	Built-in Microphone
Lens	2.8 mm
Min. Illumination	0.01 Lux @(F2.0, AGC On)
Angle of View	Horizontal Fov 102°, Vertical Fov 53°, Diagonal Fov 123°
Number of Infrared LEDs	2 pcs
Night Vision Distance	Up to 100 ft/30 m
DNR	3D DNR
Wide Dynamic Range	120 dB WDR
Network Storage	Local Storage & NAS (NFS, SMB/CIFS)
ONVIF	Support
Day/Night Switch	Day, Night, Auto, Schedule
Ethernet	RJ45 X1 (10 M/100 M)
Housing	Plastic & Metal
Color	White
Operating Power	PoE (802.3af), 12 V DC ± 25%
Storage	Built-in MicroSD/SDHC/SDXC Slot, up to 256 GB
Hardware Reset	Yes
Operating Temperature	-22 °F ~ 140 °F/30 °C ~ 60 °C
Indoor/Outdoor	Indoor/Outdoor
Weatherproof Rating	IP67
Dimension (L X W X H)	Ø110 X 81.25 mm (Ø4.33" X 3.20")
Weight	0.9 lb./390 g

ANNKE C800 Dome No-Audio Version Specifications (Model Number: I918E)	
Image Sensor	1/2.5" Sony Progressive Scan CMOS
Video Resolution	8MP (3840 X 2160@15 fps)
Signal System	PAL/NTSC
Video Compression	H.265/H.264
Video Bitrate	32 Kbps - 16 Mbps
Lens	4 mm
Min. Illumination	0.01 Lux @(F1.2, AGC On)
Angle of View	79°
Number of Infrared LEDs	3 pcs
Night Vision Distance	Up to 100 ft/30 m
DNR	3D DNR
Wide Dynamic Range	Digital WDR
ONVIF	Support
IR-Cut Filter	Yes
Ethernet	RJ45 X1 (10 M/100 M)
Housing	Metal & Plastic
Color	White
Operating Power	DC 12 V; PoE (802.3af)
Operating Temperature	-22 °F ~ 140 °F/30 °C ~ 60 °C
Indoor/Outdoor	Indoor/Outdoor
Weatherproof Rating	IP67
Vandal-Proof Rating	IK10
Dimension	4.4" X 3.2"/111 X 82.4 mm
Weight	1.1 lbs./500 g

ANNKE C800 Dome Audio Version Specifications (Model Number: I918N)	
Image Sensor	1/2.5" Progressive Scan CMOS
Video Resolution	50 Hz: 12.5 fps (3840 X 2160, 2560 X 1440, 1920 X 1080, 1280 X 720) 60 Hz: 15 fps (3840 X 2160, 2560 X 1440, 1920 X 1080, 1280 X 720)
Sub Stream	50 Hz: 25 fps (640 X 480, 640 X 360) 60 Hz: 30 fps (640 X 480, 640 X 360)
Video Compression	H.265+/H.265
Video Bitrate	32 Kbps ~ 16 Mbps
Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/MP3/AAC
Audio Input/Output	Built-in Microphone
Lens	2.8 mm
Min. Illumination	0.01 Lux @(F2.0, AGC On)
Angle of View	Horizontal Fov 102°, Vertical Fov 53°, Diagonal Fov 123°
Number of Infrared LEDs	2 pcs
Night Vision Distance	Up to 100 ft/30 m
DNR	3D DNR
Wide Dynamic Range	120 dB WDR
Network Storage	Local Storage & NAS (NFS, SMB/CIFS)
ONVIF	Support
Day/Night Switch	Day, Night, Auto, Schedule
Ethernet	RJ45 X1 (10 M/100 M)
Housing	Aluminum Alloy for Main Body
Color	White
Operating Power	PoE (802.3af), 12 V DC ± 25%
Storage	Built-in MicroSD/SDHC/SDXC Slot, up to 256 GB
Hardware Reset	Yes
Operating Temperature	-22 °F ~ 140 °F/30 °C ~ 60 °C
Indoor/Outdoor	Indoor/Outdoor
Weatherproof Rating	IP67 & IK10
Dimension (L X W X H)	Ø120 X 92.2 mm (4.7" X 3.6")
Weight	0.9 lb./420 g